
## UNTITLED READING LINEAR

Bernhard Osann

A definitive synthesis of mechanics and lighting technology, this design is clean and essential, with miniaturized joints that allow for extreme flexibility of movement. The Linear version has been designed explicitly with optics to ensure maximum visual comfort in work environments.



## 2700K

		29	L
LAMPING			10
Source	linear LED		
Total power	7W		
Emission	direct		
Switching	dimmable on board		
Tension	120V		
Color temperature	2700K		
Luminous flux	485lm	بح <u>Ø0,5</u>	
Typ CRI	90	4	
IP class	20		
Dimensions	32.3'x 43.3'		
Notes	cable length 6.6', 155° joint rotation, black RAL 9005,		
	3500K and 4000K available on request		
Codes	Structure		
UNT LN2 2A	black		

Certificazioni



## 3000K

		I	29	L
LAMPING		_	K	<u></u>
Source	linear LED			
Total power	7W			
Emission	direct			
Switching	dimmable on board			
Tension	120V			
Color temperature	3000K			
Luminous flux	485lm	45	Ø0,5	
Typ CRI	90			
IP class	20			
Dimensions	32.3'x 43.3'			
Notes	cable length 6.6', 155° joint rotation, black RAL 9005,			
	3500K and 4000K available on request			
Codes	Structure		<b>-</b> - <b>O</b>	
UNT LNN 2A	black	6	e,0 0	

Certificazioni

