

NEMO

Luminaire

Code ALB EHW 54
Name AS41C Led 14W


Measurem.

Code AS41C032019
Name AS41C Led 14W

| | | | | | | | |
|----------------------------|-------------|---------------------|-----------------------------|--------------------|----------------|------------|-----------------|
| Luminaire Flux | 1482.30 lm | Luminaire Power | 14.00 W | Efficacy | 105.88 lm/W | Efficiency | 97.46% |
| Lamps Flux | 1521.00 lm | Maximum value | 209.41 cd/klm | Position | C=0.00 G=14.00 | CG | Rotosymmetrical |
| Round Luminaire | Diam. | 450 mm | Height | 330 mm | | | |
| Round Luminous Area | Diam. | 450 mm | Height | 330 mm | | | |
| Horizontal Luminous Area | 0.159043 m2 | | Emitting area on Plane 180° | | 0.148500 m2 | | |
| Emitting area on Plane 0° | 0.148500 m2 | | Emitting area on Plane 270° | | 0.148500 m2 | | |
| Emitting area on Plane 90° | 0.148500 m2 | | Glare area at 76° | | 0.182565 m2 | | |
| Coordinate system | CG | Symmetry Type | | Rotosymmetrical | | | |
| Date | 27-01-2000 | Maximum Gamma Angle | | 180 | | | |
| Measurement Distance | 0.00 | Measurement Flux | | 1521.00 lm | | | |
| Operator | | | | Source Voltage [V] | 120.00 V | | |
| Temperature | 25.00 °C | Source current [A] | | | | | |
| Humidity | 60.00 % | Photocell | | | | | |
| Notes | | | | | | | |

| Line | | Code | Luminaire Lamps | | Flux [lm] | Pow. [W] | Q.ty |
|--------|-----------------|-------------|---------------------|------------|-----------|----------|------|
| | | Led E27 14W | Name Led E27 14W | | 1521.00 | 14.00 | 1 |
| C.I.E. | 39 75 93 83 97 | | | D DIN 5040 | B21 | | |
| F UTE | 0.81 E + 0.16 T | | | B NBN | BZ 5 | | |

Diam=450mm



Semipiani C

180.0 — 0.0

ULOR 16.15 %

DLOR 81.30 %

RN 16.57 %

