

NEMO

Luminaire

Code RCM LMM 11
Name Mini Mais Plus 2,4W


Measurerm.

Code MP032019
Name Mini Mais Plus 2,4W

Luminaire Flux	200.00 lm	Luminaire Power	2.40 W	Efficacy	83.34 lm/W	Efficiency	100.00%
Lamps Flux	200.00 lm	Maximum value	516.15 cd/klm	Position	C=5.00 G=126.00	CG	Asymmetrical
Rectangular Luminaire		Length	150 mm	Width	80 mm	Height	50 mm
Rectangular Luminous Area		Length	130 mm	Width	1 mm	Height	10 mm
Horizontal Luminous Area		0.000130 m2		Emitting area on Plane 180°		0.001300 m2	
Emitting area on Plane 0°		0.001300 m2		Emitting area on Plane 270°		0.000010 m2	
Emitting area on Plane 90°		0.000010 m2		Glare area at 76°		0.001293 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		200.00 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	Led	Name Led	200.00	2.40	1
C.I.E.	0 14 54 50 100	D DIN 5040	C11		
F UTE	--	B NBN	BZ 10		

150mm x 80mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 49.56 %

DLOR 50.45 %

RN 49.56 %

