

Installation :

Project number :Untitled Spot

Customer :NEMO

Processed by :NEMO

Date :06.10.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

1 Luminaire data

1.1 NEMO, Untitled Spot (000)

1.1.1 Data sheet

Manufacturer: NEMO

000 Untitled Spot


Luminaire data

Luminaire efficacy : 79 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 93 98 100 100 116
UGR 4H 8H Power : 20.3 / 20.3
Luminous flux : 5 W

Dimensions : Ø45 mm x 80 mm


Equipped with

Quantity : 1
Designation : LED
Colour : 3000
Luminous flux : 395 lm
Colour reproduction : 90



1.1 NEMO, Untitled Spot (000)

1.1.2 LDC




Manufacturer : NEMO
 Order number : 000
 Luminaire name : Untitled Spot
 Equipment : 1 x LED 5 W / 395 lm
 Dimensions : D 45 mm x H 80 mm
 File name : Untitled Spot.LDT

Luminaire efficacy : 79 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 30.2° C0-C180

1.1 NEMO, Untitled Spot (000)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO
 Order number : 000
 Luminaire name : Untitled Spot
 Equipment : 1 x LED 5 W / 395 lm
 Dimensions : D 45 mm x H 80 mm
 File name : Untitled Spot.LDT

Luminaire efficacy : 79 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 30.2° C0-C180