


ELLISSE PENDANT DOUBLE

Federico Palazzari

Realised in various versions through an innovative technology developed by Nemo for coupling extrusions, Ellisse guarantees diffused direct and indirect lighting with the LED housed within the structure while remaining unobtrusive. The design is linear and contemporary, while an elegant black marble base becomes a pedestal for the floor version.



2700K

LAMPING

Source	Linear LED
Total power	70W
Emission	diffused uplight (minor), diffused downlight (major)
Switching	dimnable
Tension	120V
Color temperature led	2700K
Luminous flux led	1980 +1300lm
Typ CRI	85
Ip class	20
Dimensions	53.1' x 27.6' x 0.8'
Materials	Aluminum + PC
Notes	adjustable cable length 8.2' max, 3500K and 4000K available on request, integral driver dual capability TRIAC- ELV and 0-10V, extra cable on request
Net lamp weight	11 lbs

Codes

- ELP LW2 56
- ELP LN2 56
- ELP LO2 56
- ELP LL2 56
- ELP LGW 56


Structure

- white
- black
- gold painted
- polished aluminium
- gold polished anodized

PACKAGE

Package 01	Dimension: 31.5 x 59.1 x 5.9 inches / Net weight: 12 lbs / Gross weight: 16.5 lbs
------------	--

Certificazioni



3000K

LAMPING

Source	Linear LED
Total power	70W
Emission	diffused uplight (minor), diffused downlight (major)
Switching	dimnable
Tension	120V
Color temperature led	3000K
Luminous flux led	1980 +1300lm
Typ CRI	85
Ip class	20
Dimensions	53.1 x 27.6 x .8
Materials	Aluminum + PC
Notes	adjustable cable length 8.2' max, 3500K and 4000K available on request, integral driver dual capability TRIAC- ELV and 0-10V, extra cable on request
Net lamp weight	11 lbs

Codes

ELP LWW 56
ELP LNW 56
ELP LOW 56
ELP LLW 56

Structure

white
black
gold painted
polished aluminium

PACKAGE

Package 01	Dimension: 31.5 x 59.1 x 5.9 inches / Net weight: 12 lbs / Gross weight: 16.5 lbs
------------	--

Certificazioni

