

LUX 12

Lux 12 ist eine Familie von Micro-LED-Einbaustrahlern für Außenanwendungen.

Erhältlich mit satiniertem verchromtem Messing-. Ausgestattet mit fixierter Optik und in drei Farbtemperaturen erhältlich.

Wasserdichte Kabelverschraubung aus synthetischem Material. Die Befestigung erfolgt durch ABS-Schalung (nicht im Lieferumfang).



BRASS | 3000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	3000K
Luminous flux	44lm
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 90
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg

Codes

BLUX05010170CS


Structure

grey

PACKAGE

Package 01 Dimension: 15x11x3,5 cm / Gross weight: 0,12 kg

Certificazioni



| 4,5 |



| Ø 2,6 |

BRASS | 4000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg

Codes

BLUX0501017WCS

Structure


grey

PACKAGE

Package 01

Dimension: 15x11x3,5 cm / Gross weight: 0,12 kg

Certificazioni



| 4,5 |



| Ø 2,6 |

BRASS | 5000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	5000K
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	70
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg

Codes

BLUX0501017NCS


Structure

grey

PACKAGE

Package 01 Dimension: 15x11x3,5 cm / Gross weight: 0,09 kg

Certificazioni



| 4,5 |



| Ø 2,6 |