RIGA TRANSPARENT

RIGA is a product family with a selection of flexible LED strips for outdoor use, particularly suitable for decorative lighting. Riga is composed by a 24V LED strip embedded in a white PVC profile and encapsulated in a transparent polyurethane resin, extremely resistable to any weather condition and with an excellent stability against UV rays. The transparent resin version emitts frontal light. Riga is available in various standard lengths. 3500K and 4000K on request.

The installation can be done with clips (included).



www.nemolighting.com RIGA TRANSPARENT - 1 / 6

LAMPING

Source Flexible linear LED

Total power 9,6W Emission Direct 120° Tension 24VDC 2700K Color temperature Luminous flux 1400lm Initial luminaire efficacy 150lm/W Initial chromaticity SDCM < 3

Typ CRI 85 IP class 68

1,5x0,7x100cm **Dimensions** Materials Resin + PVC Ambient temperature range - 20° / 55° 25°

Performance ambient temperature

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

2m; driver not included

Customization options Lengths

Accessories Connectors kit IP68, | Drivers 24VDC + DALI interface,

Net lamp weight 0,21 kg


Codes Structure MRIG0910035DRE white

PACKAGE

Package 01 Dimension: 22x19x8 cm / Gross weight: 0,81 kg

Certificazioni







LAMPING

Source Flexible linear LED

19,2W Total power Emission Direct 120° Tension 24VDC 2700K Color temperature Luminous flux 2800lm Initial luminaire efficacy 150lm/W Initial chromaticity SDCM < 3 Typ CRI 85

 $\begin{array}{lll} \mbox{IP class} & \mbox{68} \\ \mbox{Dimensions} & \mbox{1,5x0,7x200cm} \\ \mbox{Materials} & \mbox{Resin + PVC} \\ \end{array}$

Ambient temperature range - 20° / 55°

Performance ambient temperature 25°

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

2m; driver not included

Customization options Lengths

Accessories Connectors kit IP68, | Drivers 24VDC + DALI interface,

Net lamp weight 0,48 kg


Codes Structure
MRIG0920035DRE white

PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 0,84 kg

Certificazioni







LAMPING

Source Flexible linear LED

Total power28,8WEmissionDirect 120°Tension24VDCColor temperature2700KLuminous flux4200lmInitial luminaire efficacy150lm/WInitial chromaticitySDCM < 3</th>

Typ CRI 85 IP class 68

Dimensions1,5x0,7x300cmMaterialsResin + PVCAmbient temperature range- 20° / 55°Performance ambient temperature25°

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

2m; driver not included

Customization options Lengths

Accessories Connectors kit IP68, | Drivers 24VDC + DALI interface,

Net lamp weight 0,72 kg


Codes Structure
MRIG0930035DRE white

PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,08 kg

Certificazioni

CE CE





LAMPING

Source Flexible linear LED

Total power 38,4W Emission Direct 120° Tension 24VDC 2700K Color temperature Luminous flux 5600lm Initial luminaire efficacy 150lm/W Initial chromaticity SDCM < 3

Typ CRI 85 IP class 68

1,5x0,7x400cm **Dimensions** Materials Resin + PVC Ambient temperature range - 20° / 55° 25°

Performance ambient temperature

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

2m; driver not included

Customization options Lengths

Accessories Connectors kit IP68, | Drivers 24VDC + DALI interface,

Net lamp weight 0,96 kg


Codes Structure MRIG0940035DRE white

PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,32 kg

Certificazioni







LAMPING

Source Flexible linear LED

Total power 48W

EmissionDirect 120°Tension24VDCColor temperature2700KLuminous flux7000lmInitial luminaire efficacy60lm/WInitial chromaticitySDCM < 3</td>

Typ CRI 85 IP class 68

 $\begin{array}{ll} \text{Dimensions} & 1,5\text{x}\,0,7\text{x}\,5\,0\,0\,\text{cm} \\ \text{Materials} & \text{Resin} + \text{PVC} \\ \text{Ambient temperature range} & -20^{\circ}\,/\,55^{\circ} \end{array}$

Performance ambient temperature 25°

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

2m; driver not included

Customization options Lengths

Accessories Connectors kit IP68, | Drivers 24VDC + DALI interface,

Net lamp weight 1,2 kg

Codes Structure
MRIG0950035DRE white

PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 0,99 kg

Certificazioni

C€ EA

