

FLEX CEILING

FLEX is a family of miniaturized adjustable spots dedicated to accent lighting.

Available in numerous fixings, optics and finishes to fulfil any installation requirement. The FLEX Collection is composed of FLEX CEILING with a fixed and variable optic, different beam angles and in black, gold, anodized grey and bronze grey finish, and FLEX TRACK, a magnetic/mechanic spot system in black anodized aluminium. The integrated aluminium joint allows fixation and orientation without any visible cable.



FIXED OPTIC | 3000K - 20°

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct 20°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x8cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21WAN
BFLE0401F21WAO
BFLE0401F21WAA
BFLE0401F21WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01 Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 3000K - 30°

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct 30°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x8cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421WAN
BFLE0401421WAO
BFLE0401421WAA
BFLE0401421WAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01 Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 20°

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct 20°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	362lm
Initial luminaire efficacy	86lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x8cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401F21NAN
BFLE0401F21NAO
BFLE0401F21NAA
BFLE0401F21NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01 Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



FIXED OPTIC | 4000K - 30°

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct 30°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	323lm
Initial luminaire efficacy	77lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x8cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	25°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,11 kg

Codes

BFLE0401421NAN
BFLE0401421NAO
BFLE0401421NAA
BFLE0401421NAB

Structure

black
gold
grey
bronze grey

PACKAGE

Package 01 Dimension: 11,5x11x8 cm / Gross weight: 0,15 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 3000K

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	76lm (45°)
Initial luminaire efficacy	19lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x10,7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,10 kg

Codes

BFLE0401921WAN

Structure

black

PACKAGE

Package 01 Dimension: 11,5x11x8 cm / Gross weight: 0,14 kg


Certificazioni



FIXED OPTIC



ZOOM OPTIC



ZOOM OPTIC | 4000K

LAMPING

Source	LED spot
Total power	4,2W
Emission	Direct adjustable 15°-45°
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	80lm
Initial luminaire efficacy	19lm/W
Initial chromaticity	SDCM < 3
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	ø3,3x10,7cm
Materials	Anodized aluminum
Ambient temperature range	- 20° / 25°
Performance ambient temperature	20°
Notes	driver not included
Customization options	1-10V, DALI, DMX, Casambi, CCT 2700K
Accessories	Drivers 350mA,
Net lamp weight	0,10 kg

Codes

BFLE0401921NAN

Structure

black

PACKAGE

Package 01

Dimension: 11,5x11x8 cm / Gross weight: 0,14 kg

Certificazioni



FIXED OPTIC



ZOOM OPTIC

