

RIGA INDOOR

Flexible LED strip for indoor applications.

Riga indoor is composed by a 12V LED strip

encapsulated in transparent polyurethane

resin. Available in warm white and blue light.

Riga indoor is provided in a 5m reel.

The installation can be done with double-sided tape already affixed.



3000K | 5M

LAMPING

Source	LED strip
Total power	25W
Emission	Direct orientable
Tension	12VDC
Color temperature	3000K
Luminous flux	350lm/m
Initial luminaire efficacy	70lm/W
Initial chromaticity	SDCM < 5
Typ CRI	> 80
IP class	65
Dimensions	500x0,8x0,3cm
Materials	Resin
Ambient temperature range	-20°C / 40°C
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 0,25m; driver not included
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	1,2 kg

Codes

MRIG0450006WRE


Structure

transparent

PACKAGE

Package 01 Dimension: 32x30x12,5 cm / Gross weight: 1,32 kg

Certificazioni



BLUE | 5M

LAMPING

Source	LED strip
Total power	25W
Emission	Direct orientable
Tension	12VDC
Color temperature	blue
Initial luminaire efficacy	< 20lm/W
Typ CRI	> 80
IP class	65
Dimensions	500x0,8x0,3cm
Materials	Resin
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 0,25m; driver not included
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	1,2 kg

Codes

MRIG04500061RE


Structure

transparent

PACKAGE

Package 01 Dimension: 32x30x12,5 cm / Gross weight: 1,32 kg

Certificazioni



RGB | 5M

LAMPING

Source	LED strip
Total power	37,5W
Emission	Direct orientable
Tension	12VDC
Color temperature	RGB
Typ CRI	> 80
IP class	65
Dimensions	500x0,8x0,3cm
Materials	Resin
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 0,25m; driver not included
Accessories	Drivers 12VDC + DALI interface,
Net lamp weight	1,2 kg

Codes

MRIG04500065RE

Structure

transparent

PACKAGE

Package 01

Dimension: 32x30x12,5 cm / Gross weight: 1,32 kg

Certificazioni

