

# LUX RECESSED

The LUX collection, characterized by small spots for outdoor applications, is enriched with more powerful versions to meet the need for a more powerful lighting.

Lux Recessed, suitable for façade lighting and path, is available in different lumen package dedicated to specific application needs, finishes, color temperatures and beam angles.



4,2W | 3000K - 17°

## LAMPING

Source	LED
Total power	4.2W
Emission	direct
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	366lm
Initial luminaire efficacy	87lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	Ø5.25x7
Materials	anodized aluminum
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable 1m, recessed box LUXCASSA4 not included, driver not included. compatible control: 1-10V, DALI, DMX, Casambi
Customization options	2700K
Accessories	Drivers 350mA,   Recessed box, Recessed box cassa 4
Net lamp weight	0.28 kg

## Codes

BLUR1901N21WAA  
BLUR1901N21WAN

## Structure/Diffuser

grey/transparent diffuser  
black/transparent diffuser


## PACKAGE

Package 01 Dimension: 11,50x11x8 cm / Gross weight: 0,32 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |

4,2W | 3000K - 46°

## LAMPING

Source	LED
Total power	4.2W
Emission	direct
Switching	according to driver
Tension	350mA
Color temperature	3000K
Luminous flux	372lm
Initial luminaire efficacy	89lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	Ø5.25x7
Materials	anodized aluminum
Ambient temperature range	-20°C/35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable 1m, recessed box LUXCASSA4 not included, driver not included. compatible control: 1-10V, DALI, DMX, Casambi
Customization options	2700K
Accessories	Drivers 350mA,   Recessed box, Recessed box cassa 4
Net lamp weight	0.28 kg

## Codes

BLUR1901F21WAA  
BLUR1901F21WAN

## Structure/Diffuser

grey/transparent diffuser  
black/transparent diffuser


## PACKAGE

Package 01 Dimension: 11,50x11x8 cm / Gross weight: 0,32 kg

## Certificazioni



LUX RECESSED 4,2W




7



Ø 5,2

LUX RECESSED 12W



9,4

7,6



Ø 12,4

4,2W | 4000K - 17°

## LAMPING

Source	LED
Total power	4.2W
Emission	direct
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	366lm
Initial luminaire efficacy	87lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	67
Dimensions	Ø5.25x7
Materials	anodized aluminum
Ambient temperature range	-20°C/35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable 1m, recessed box LUXCASSA4 not included, driver not included. compatible control: 1-10V, DALI, DMX, Casambi
Customization options	2700K
Accessories	Drivers 350mA,   Recessed box, Recessed box cassa 4
Net lamp weight	0.28 kg

## Codes

BLUR1901N21NAA  
BLUR1901N21NAN

## Structure/Diffuser

grey/transparent diffuser  
black/transparent diffuser


## PACKAGE

Package 01 Dimension: 11,50x11x8 cm / Gross weight: 0,32 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |

4,2W | 4000K - 46°

## LAMPING

Source	LED
Total power	4.2W
Emission	direct
Switching	according to driver
Tension	350mA
Color temperature	4000K
Luminous flux	372lm
Initial luminaire efficacy	89lm/W
Initial chromaticity	SDCM<3
Typ CRI	90
IP class	90
Dimensions	Ø5.25x7
Materials	anodized aluminum
Ambient temperature range	-20°C/35°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable 1m, recessed box LUXCASSA4 not included, driver not included. compatible control: 1-10V, DALI, DMX, Casambi
Customization options	2700K
Accessories	Drivers 350mA,   Recessed box, Recessed box cassa 4
Net lamp weight	0.28 kg

## Codes

BLUR1901F21NAA  
BLUR1901F21NAN

## Structure/Diffuser

grey/transparent diffuser  
black/transparent diffuser


## PACKAGE

Package 01 Dimension: 11,50x11x8 cm / Gross weight: 0,32 kg

## Certificazioni



LUX RECESSED 4,2W




7




Ø 5,2

LUX RECESSED 12W



9,4

7,6



Ø 12,4

12W | 2700K - 14°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to driver
Tension	350mA
Color temperature	2700K
Luminous flux	1040lm
Initial luminaire efficacy	87lm/W
Initial chromaticity	SDCM<3
Typ CRI	>90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	

Net lamp weight 1 kg

## Codes

BLUR1901N43DAA  
BLUR1901N43DAN

## Structure

grey  
black


## PACKAGE

Package 01 Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |

12W | 2700K - 53°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to bulb
Tension	350mA
Color temperature	2700K
Luminous flux	900lm
Initial luminaire efficacy	75lm/W
Initial chromaticity	SDCM<3
Typ CRI	>90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	

Net lamp weight

1 kg

## Codes

BLUR1901H43DAA

BLUR1901H43DAN

## Structure

grey

black

## PACKAGE


Package 01

Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |

12W | 3000K - 14°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to bulb
Tension	350mA
Color temperature	3000K
Luminous flux	1100lm
Initial luminaire efficacy	92lm/W
Initial chromaticity	SDCM<3
Typ CRI	>90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	

Net lamp weight

1 kg

## Codes

BLUR1901N43WAA  
BLUR1901N43WAN

## Structure

grey  
black

## PACKAGE


Package 01

Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni





LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |



12W | 3000K - 53°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to bulb
Tension	350mA
Color temperature	3000K
Luminous flux	950lm
Initial luminaire efficacy	80lm/W
Initial chromaticity	SDCM<3
Typ CRI	>90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable length 2m, BLUXR12BOX and BLUXHC66 not included, driver not included. Compatible control: 1-10V, DALI, TRIAC, series connection
Net lamp weight	1 kg

## Codes

BLUR1901H43WAA  
BLUR1901H43WAN

## Structure

grey  
black


## PACKAGE

Package 01 Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni



LUX RECESSED 4,2W




7



Ø 5,2

LUX RECESSED 12W



9,4

7,6



Ø 12,4

12W | 4000K - 14°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to bulb
Tension	350mA
Color temperature	4000K
Luminous flux	1200lm
Initial luminaire efficacy	100lm/W
Initial chromaticity	SDCM<3
Typ CRI	>90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	cable length 2m, BLUXR12BOX and BLUXHC66 not included, driver not included. Compatible control: 1-10V, DALI, TRIAC, series connection
Net lamp weight	1 kg

## Codes

BLUR1901N43NAA  
BLUR1901N43NAN

## Structure

grey  
black


## PACKAGE

Package 01 Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |

12W | 4000K - 53°

## LAMPING

Source	LED spot
Total power	12W
Emission	direct
Switching	according to bulb
Tension	350mA
Color temperature	4000K
Luminous flux	1050lm
Initial luminaire efficacy	88lm/W
Initial chromaticity	SDCM<3
Typ CRI	<90
IP class	67
Dimensions	ø12,4x9,4
Ambient temperature range	-20°C/35°
Performance ambient temperature	25°C
Mechanical impact protection code	IK10
Notes	

Net lamp weight

1 kg

## Codes

BLUR1901H43NAA  
BLUR1901H43NAN

## Structure

grey  
black

## PACKAGE


Package 01

Dimension: 23,50x15x11 cm / Gross weight: 1,15 kg

## Certificazioni




LUX RECESSED 4,2W



| Ø 5,2 |

LUX RECESSED 12W



| Ø 12,4 |