

# ZIRKOL SQUARE PLUS

ZIRKOL S Plus est une famille de luminaires carré suspendus idéale pour l'éclairage général et décoratif.

Corps en aluminium anodisé et écran de protection opale pour un éclairage homogène. IRC > 80. L'émission de la lumière peut être directe ou directe/indirecte avec un haut flux lumineux et différente température de couleur. Alimentation déportée incluse.



## 1X1M | DOWNLIGHT - 3000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 75W                                                                                                 |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 7600lm                                                                                              |
| Initial luminaire efficacy      | 100lm/W                                                                                             |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 100x100x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 5,7 kg                                                                                              |

### Codes

PZRS0310G15WNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 75W                                                                                                           |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 3000K                                                                                                         |
| Luminous flux                   | 7600lm                                                                                                        |
| Initial luminaire efficacy      | 80lm/W                                                                                                        |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 100x100x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 5,7 kg                                                                                                        |

### Codes

PZRS1610G15WNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 3000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 150W                                                                                                |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 4800lm + 7600lm                                                                                     |
| Initial luminaire efficacy      | 80lm/W                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 100x100x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 5,7 kg                                                                                              |

### Codes

PZRS1410G15WNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 150W                                                                                                          |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 3000K                                                                                                         |
| Luminous flux                   | 4800lm + 7600lm                                                                                               |
| Initial luminaire efficacy      | 100lm/W                                                                                                       |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 100x100x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 5,7 kg                                                                                                        |

### Codes

PZRS1710G15WNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | DOWNLIGHT - 4000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 75W                                                                                                 |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 7600lm                                                                                              |
| Initial luminaire efficacy      | 100lm/W                                                                                             |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 100x100x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 5,7 kg                                                                                              |

### Codes

PZRS0310G15NNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 75W                                                                                                           |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 4000K                                                                                                         |
| Luminous flux                   | 7600lm                                                                                                        |
| Initial luminaire efficacy      | 80lm/W                                                                                                        |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 100x100x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 5,7 kg                                                                                                        |

### Codes

PZRS1610G15NNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni



## 1X1M | UP - DOWNLIGHT - 4000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 150W                                                                                                |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 4800lm + 7600lm                                                                                     |
| Initial luminaire efficacy      | 80lm/W                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 100x100x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 5,7 kg                                                                                              |

### Codes

PZRS1410G15NNE


### Structure

black

### PACKAGE

|            |                                                 |
|------------|-------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 9,12 kg |
|------------|-------------------------------------------------|

### Certificazioni





## 1X1M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 150W                                                                                                          |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 4000K                                                                                                         |
| Luminous flux                   | 4800lm + 7600lm                                                                                               |
| Initial luminaire efficacy      | 100lm/W                                                                                                       |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 100x100x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 5,7 kg                                                                                                        |

### Codes

PZRS1710G15NNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 105x105x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 3000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 112,5W                                                                                              |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 11000lm                                                                                             |
| Initial luminaire efficacy      | 100lm/W                                                                                             |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 150x150x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 8,56 kg                                                                                             |

### Codes

PZRS0315G15WNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 3000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 112,5W                                                                                                        |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 3000K                                                                                                         |
| Luminous flux                   | 11000lm                                                                                                       |
| Initial luminaire efficacy      | 82lm/W                                                                                                        |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 150x150x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 8,56 kg                                                                                                       |

### Codes

PZRS1615G15WNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 3000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 225W                                                                                                |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 3000K                                                                                               |
| Luminous flux                   | 7200lm + 11000lm                                                                                    |
| Initial luminaire efficacy      | 82lm/W                                                                                              |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 150x150x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 8,56 kg                                                                                             |

### Codes

PZRS1415G15WNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 3000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 225W                                                                                                          |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 3000K                                                                                                         |
| Luminous flux                   | 7200lm + 11000lm                                                                                              |
| Initial luminaire efficacy      | 100lm/W                                                                                                       |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 150x150x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 8,56 kg                                                                                                       |

### Codes

PZRS1715G15WNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 4000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 112,5W                                                                                              |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 11000lm                                                                                             |
| Initial luminaire efficacy      | 100lm/W                                                                                             |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 150x150x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 0°C / 35°                                                                                           |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                       |
| Net lamp weight                 | 8,56 kg                                                                                             |

### Codes

PZRS0315G15NNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | DOWNLIGHT - 4000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 112,5W                                                                                                        |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 4000K                                                                                                         |
| Luminous flux                   | 11000lm                                                                                                       |
| Initial luminaire efficacy      | 82lm/W                                                                                                        |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 150x150x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 0°C / 35°                                                                                                     |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes                                                                                                 |
| Net lamp weight                 | 8,56 kg                                                                                                       |

### Codes

PZRS1615G15NNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni



## 1,5X1,5M | UP - DOWNLIGHT - 4000K - HIGH FLUX

### LAMPING

|                                 |                                                                                                     |
|---------------------------------|-----------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                          |
| Total power                     | 225W                                                                                                |
| Emission                        | Diffused orientable                                                                                 |
| Tension                         | 24VDC                                                                                               |
| Color temperature               | 4000K                                                                                               |
| Luminous flux                   | 7200lm + 11000lm                                                                                    |
| Initial luminaire efficacy      | 82lm/W                                                                                              |
| Initial chromaticity            | SDCM < 3                                                                                            |
| Typ CRI                         | > 80                                                                                                |
| IP class                        | 40                                                                                                  |
| Dimensions                      | 150x150x5cm                                                                                         |
| Materials                       | Aluminium                                                                                           |
| Ambient temperature range       | 20°C / 35°                                                                                          |
| Performance ambient temperature | 25°                                                                                                 |
| Notes                           | remote driver included; suspension kit included; cable 5m;<br>optional controls: DALI, DMX, Casambi |
| Customization options           | Shapes, sizes, colour temperatures, RGB, RGBW                                                       |
| Net lamp weight                 | 8,56 kg                                                                                             |

### Codes

PZRS1415G15NNE


### Structure

black

### PACKAGE

|            |                                                  |
|------------|--------------------------------------------------|
| Package 01 | Dimension: 155x155x5 cm / Gross weight: 12,06 kg |
|------------|--------------------------------------------------|

### Certificazioni





## 1,5X1,5M | UP - DOWNLIGHT - 4000K - DALI - HIGH FLUX

### LAMPING

|                                 |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Source                          | Linear LED                                                                                                    |
| Total power                     | 225W                                                                                                          |
| Emission                        | Diffused orientable                                                                                           |
| Switching                       | DALI                                                                                                          |
| Tension                         | 24VDC                                                                                                         |
| Color temperature               | 4000K                                                                                                         |
| Luminous flux                   | 7200lm + 11000lm                                                                                              |
| Initial luminaire efficacy      | 100lm/W                                                                                                       |
| Initial chromaticity            | SDCM < 3                                                                                                      |
| Typ CRI                         | > 80                                                                                                          |
| IP class                        | 40                                                                                                            |
| Dimensions                      | 150x150x5cm                                                                                                   |
| Materials                       | Aluminium                                                                                                     |
| Ambient temperature range       | 20°C / 35°                                                                                                    |
| Performance ambient temperature | 25°                                                                                                           |
| Notes                           | remote driver and DALI interface included; suspension kit included; cable 5m; optional controls: DMX, Casambi |
| Customization options           | Shapes, sizes, colour temperatures, RGB, RGBW                                                                 |
| Net lamp weight                 | 8,56 kg                                                                                                       |

### Codes

PZRS1715G15NNE

### Structure

black

### PACKAGE

Package 01      Dimension: 155x155x5 cm / Gross weight: 1,25 kg

### Certificazioni

