

LUX 12

Lux 12 est une famille de micro spot LED encastré pour extérieur.

Disponible en laiton chromé satiné. Equipé d'une optique fixe et est disponible en trois températures de couleur. Presse-étoupe étanche en matériel synthétique. L'installation se fait à l'aide d'un pot d'encastrement en ABS non inclus.



BRASS | 3000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	3000K
Luminous flux	44lm
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 90
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg


Codes
BLUX05010170CS

Structure
grey

PACKAGE

Package 01 Dimension: 15x11x3,5 cm / Gross weight: 0,12 kg

Certificazioni



| 4,5 |



| Ø 2,6 |

BRASS | 4000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	4000K
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	> 80
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg

Codes

BLUX0501017WCS


Structure

grey

PACKAGE

Package 01 Dimension: 15x11x3,5 cm / Gross weight: 0,12 kg

Certificazioni



| 4,5 |



| Ø 2,6 |

BRASS | 5000K - 60°

LAMPING

Source	LED spot
Total power	1,2W
Emission	Direct adjustable
Tension	350mA
Color temperature	5000K
Initial luminaire efficacy	35lm/W
Initial chromaticity	SDCM < 3
Typ CRI	70
IP class	68
Dimensions	2,5x4,5cm
Materials	Sanded chromed brass
Ambient temperature range	-20°C / 35°C
Performance ambient temperature	25°C
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 1m; driver not included, recessed box LUXCASSA5
Accessories	Drivers 350mA, Recessed box, Recessed box cassa 5
Net lamp weight	0,11 kg

Codes

BLUX0501017NCS


Structure

grey

PACKAGE

Package 01 Dimension: 15x11x3,5 cm / Gross weight: 0,09 kg

Certificazioni



| 4,5 |



| Ø 2,6 |