

SALINA

Familie von Downlight-Einbauleuchten für Akzentbeleuchtung.

Die Leuchte kann um 30° vertikal und um 355° horizontal rotiert werden, um die Beleuchtung in jede beliebige Ausrichtung zu lenken.

Modulare Leuchte mit Aussenringen in verschiedenen Oberflächen, leicht montier- und austauschbar mit verschiedenen Abstrahlwinkeln.



RECESSED TRIMLESS 15° | 2700K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	270mA
Color temperature	2700K
Luminous flux	640lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø7,1x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,27 kg

Codes

SAL LW2 61

Structure

white

PACKAGE



Package 01

Dimension: 46x42x22 cm / Gross weight: 0,31 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 15° | 3000K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	270mA
Color temperature	2700K
Luminous flux	740lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø7,1x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,27 kg

Codes

SAL LW3 61

Structure

white

PACKAGE



Package 01

Dimension: 46x42x22 cm / Gross weight: 0,31 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 35° | 3000K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	270mA
Color temperature	3000K
Luminous flux	770lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø7,1x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,27 kg

Codes

SAL LW3 63

Structure

white

PACKAGE



Package 01

Dimension: 46x42x22 cm / Gross weight: 0,31 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIMLESS 35° | 2700K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	270mA
Color temperature	2700K
Luminous flux	670lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø7,1x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,27 kg

Codes

SAL LW2 63

Structure

white

PACKAGE



Package 01

Dimension: 46x42x22 cm / Gross weight: 0,31 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 15° | 2700K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	270mA
Color temperature	2700K
Luminous flux	700lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø8,5x9cm
Accessories	Drivers, Salina Ring,
Net lamp weight	0,31 kg

Codes

SAT LW2 61

SAT LN2 61

Structure

white

black

PACKAGE



Package 01

Dimension: 50,8x41,5x22 cm / Gross weight: 0,34 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 15° | 3000K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 15°
Switching	according to driver
Tension	270mA
Color temperature	3000K
Luminous flux	700lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø8,5x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,31 kg

Codes

SAT LW3 61

SAT LN3 61

Structure

white

black

PACKAGE



Package 01

Dimension: 50,8x41,5x22 cm / Gross weight: 0,34 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 35° | 3000K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	270mA
Color temperature	3000K
Luminous flux	700lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø8,5x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,31 kg

Codes

SAT LW3 63
SAT LN3 63

Structure

white
black

PACKAGE



Package 01

Dimension: 50,8x41,5x22 cm / Gross weight: 0,34 kg



Certificazioni



TRIMLESS



TRIM



RECESSED TRIM 35° | 2700K

LAMPING

Source	LED spot
Total power	10W
Emission	Direct adjustable 35°
Switching	according to driver
Tension	270mA
Color temperature	2700K
Luminous flux	700lm
Typ CRI	> 90
Energy class	F
IP class	20
Dimensions	ø8,5x9cm
Notes	driver and ring not included
Accessories	Drivers, Salina Ring,
Net lamp weight	0,31 kg

Codes

SAT LW2 63
SAT LN2 63

Structure

white
black

PACKAGE



Package 01

Dimension: 50,8x41,5x22 cm / Gross weight: 0,34 kg

Certificazioni



TRIMLESS



TRIM

