

# ZIRKOL LINEAR UGR CEILING

La nouvelle lampe de la collection, Zirkol Linear UGR est équipé d'un groupe optique particulier qui permet un éclairage direct avec un indice d'éblouissement réduit (UGR <19). Profilé en aluminium disponible dans les finitions blanc et noir et avec des températures de couleur LED de 3000K et 4000K. Zirkol Linear UGR est maintenant présenté dans la version Ceiling, avec driver intégré et est particulièrement adapté à une application dans les bureaux et les environnements de travail, où un confort visuel élevé est requis.



## 1,4M CEILING | 3000K

---



### LAMPING

Source	linear LED
Total power	40W
Emission	direct   UGR < 19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	3600lm
Typ CRI	>90
IP class	20
Dimensions	140x2,6x5
Materials	aluminium
Notes	1 x driver Ultralim included, ceiling attachments included   RAL 9005 black   RAL 9016 white
Customization options	lengths
Net lamp weight	3,2 kg

### Codes

BZRLU414I42WBO

BZRLU414I42WNE

### Structure

white

black

### PACKAGE

Package 01

Dimension: 204x11x11 cm / Gross weight: 5 kg

### Certificazioni



## 1,4M CEILING | 4000K

---



### LAMPING

Source	linear LED
Total power	40W
Emission	direct   UGR < 19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	3700lm
Typ CRI	>90
IP class	20
Dimensions	140x2,6x5
Materials	aluminium
Notes	1 x driver Ultraslim included, ceiling attachments included   RAL 9005 black   RAL 9016 white
Customization options	lengths
Net lamp weight	3,2 kg

### Codes

BZRLU414I42NBO

BZRLU414I42NNE

### Structure

white

black

### PACKAGE

Package 01

Dimension: 204x11x11 cm / Gross weight: 5 kg

### Certificazioni

