

# RIGA OPAL

RIGA è un famiglia di prodotti che racchiude una selezione di LED strips flessibili per esterni, particolarmente adatta ad un'illuminazione decorativa. Riga è costituito da un nastro LED a 24V inguainato in un profilo in PVC bianco e incapsulato in una resina poliuretana opale, estremamente resistente agli agenti atmosferici e con un eccellente grado di stabilità se esposta a raggi UV.

Permette un'emissione laterale o frontale della luce a seconda della possibilità di curvatura della LED strip.

Riga è proposto in differenti lunghezze.

Il fissaggio può avvenire tramite staffette (incluse).



# 1M | 3000K - FRONT LIGHT

## LAMPING

Source	Flexible linear LED
Total power	9,6W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	510lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x100cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,39 kg

## Codes

MRIG0910G35WFL


## Structure

white

## PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,47 kg

## Certificazioni



## BRACKETS (included)



## 1M | 3000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	9,6W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	510lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x100cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,39 kg

### Codes

MRIG0910G35WSL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,47 kg

### Certificazioni



### BRACKETS (included)



# 1M | 4000K - FRONT LIGHT

## LAMPING

Source	Flexible linear LED
Total power	9,6W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	600lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x100cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,39 kg

## Codes

MRIG0910G35NFL


## Structure

white

## PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,47 kg

## Certificazioni



## BRACKETS (included)



# 1M | 4000K - SIDE LIGHT

## LAMPING

Source	Flexible linear LED
Total power	9,6W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	600lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x100cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,39 kg

## Codes

MRIG0910G35NSL


## Structure

white

## PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,47 kg

## Certificazioni



## BRACKETS (included)



## 2M | 3000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	19,2W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	1020lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x200cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,86 kg

### Codes

MRIG0920G35WFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,51 kg

### Certificazioni



### BRACKETS (included)



## 2M | 3000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	19,2W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	1020lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x200cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,86 kg

### Codes

MRIG0920G35WSL

### Structure

white


### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,51 kg

### Certificazioni



### RIGA OPAL



### BRACKETS (included)



## 2M | 4000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	19,2W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	1200lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x200cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,86 kg

### Codes

MRIG0920G35NFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,51 kg

### Certificazioni



### BRACKETS (included)





## 2M | 4000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	19,2W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	1200lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x200cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	0,86 kg

### Codes

MRIG0920G35NSL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,51 kg

### Certificazioni



### BRACKETS (included)



## 3M | 3000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	28,8W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	1530lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x300cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,3 kg

### Codes

MRIG0930G35WFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,94 kg

### Certificazioni



### BRACKETS (included)



## 3M | 3000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	28,8W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	1530lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x300cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,3 kg

### Codes

MRIG0930G35WSL

### Structure


white

### PACKAGE

Package 01

Dimension: 42x42x4,5 cm / Gross weight: 1,94 kg

### Certificazioni



### BRACKETS (included)



## 3M | 4000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	28,8W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	1800lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x300cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,3 kg

### Codes

MRIG0930G35NFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,94 kg

### Certificazioni



### BRACKETS (included)



## 3M | 4000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	28,8W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	1800lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x300cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,3 kg

### Codes

MRIG0930G35NSL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 1,94 kg

### Certificazioni



### BRACKETS (included)



## 4M | 3000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	38,4W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	2040lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x400cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,78 kg

### Codes

MRIG0940G35WFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 2,38 kg

### Certificazioni



### BRACKETS (included)



## 4M | 3000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	38,4W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	2040lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x400cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,78 kg

### Codes

MRIG0940G35WSL

### Structure

white


### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 2,38 kg

### Certificazioni



### RIGA OPAL



### BRACKETS (included)



## 4M | 4000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	38,4W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	2400lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x400cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,78 kg

### Codes

MRIG0940G35NFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 2,38 kg

### Certificazioni



### BRACKETS (included)





## 4M | 4000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	38,4W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	2400lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x400cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	1,78 kg

### Codes

MRIG0940G35NSL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 2,38 kg

### Certificazioni



### BRACKETS (included)



## 5M | 3000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	48W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	2550lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x500cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	2,16 kg

### Codes

MRIG0950G35WFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 0,99 kg

### Certificazioni



### BRACKETS (included)



## 5M | 3000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	48W
Emission	Diffused orientable
Tension	24VDC
Color temperature	3000K
Luminous flux	2550lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x500cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	2,16 kg

### Codes

MRIG0950G35WSL

### Structure

white


### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 0,99 kg

### Certificazioni



### RIGA OPAL



### BRACKETS (included)



## 5M | 4000K - FRONT LIGHT

### LAMPING

Source	Flexible linear LED
Total power	48W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	3000lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x500cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	2,16 kg

### Codes

MRIG0950G35NFL


### Structure

white

### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 0,99 kg

### Certificazioni



### BRACKETS (included)



## 5M | 4000K - SIDE LIGHT

### LAMPING

Source	Flexible linear LED
Total power	48W
Emission	Diffused orientable
Tension	24VDC
Color temperature	4000K
Luminous flux	3000lm
Initial luminaire efficacy	60lm/W
Initial chromaticity	SDCM < 3
Typ CRI	85
IP class	68
Dimensions	1,5x1,5x500cm
Materials	Resin + PVC
Ambient temperature range	- 20° / 55°
Performance ambient temperature	25°
Notes	compatible controls: 1-10V, DALI, DMX, Casambi; cable 2m; driver not included
Customization options	Lengths
Accessories	Connectors kit IP68,   Drivers 24VDC + DALI interface,
Net lamp weight	2,16 kg

### Codes

MRIG0950G35NSL

### Structure

white


### PACKAGE

Package 01 Dimension: 42x42x4,5 cm / Gross weight: 2,38 kg

### Certificazioni



### RIGA OPAL



### BRACKETS (included)

