

MINIFLUX LINEA OPAL

Miniflux Linea Opal è un sistema a LED a sospensione destinato all'illuminazione in interni. Corpo in profilato in alluminio su cui è posizionata una striscia di Nastro LED 24V DC. CRI>97. Diffusore in policarbonato opale per un'emissione di luce omogenea. È proposto con finitura black, red e gold. Miniflux è disponibile in due temperature colore e nelle versioni TRIAC e DALI. Alimentatore remoto incluso.



LAMPING

Source	Linear LED
Total power	15W
Emission	Direct 120°
Switching	TRIAC
Tension	24VDC
Color temperature	2700K
Initial chromaticity	SDCM<2
Typ CRI	>97
Energy class	F
IP class	40
Dimensions	Ø20 x 1060mm
Materials	Polycarbonate
Ambient temperature range	-20°C / 50°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	Driver included
Customization options	CCT 4000K on request
Net lamp weight	0.6 kg


Codes

BMLO2710G26DAN
BMLO2710G26DAR
BMLO2710G26DAO

Structure

black
red
gold

Certificazioni



LAMPING

Source	Linear LED
Total power	15W
Emission	Direct 120°
Switching	TRIAC
Tension	24VDC
Color temperature	3000K
Luminous flux	905lm
Initial luminaire efficacy	60m/W
Initial chromaticity	SDCM<2
Typ CRI	>97
Energy class	F
IP class	40
Dimensions	Ø20 x 1060mm
Materials	Polycarbonate
Ambient temperature range	-20°C / 50°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	Driver included
Customization options	CCT 4000K on request

Codes

BMLO2710G26WAN
BMLO2710G26WAR
BMLO2710G26WAO


Structure

black
red
gold

PACKAGE

Package 01 Net weight: 0.6 kg

Certificazioni



LAMPING

Source	Linear LED
Total power	15W
Emission	Direct 120°
Switching	DALI
Tension	24VDC
Color temperature	2700K
Initial chromaticity	SDCM<2
Typ CRI	>97
Energy class	F
IP class	40
Dimensions	Ø20 x 1060mm
Materials	Polycarbonate
Ambient temperature range	-20°C / 50°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	Driver included
Customization options	CCT 4000K on request
Net lamp weight	0.6 kg


Codes

BMLO1610G26DAN
BMLO1610G26DAR
BMLO1610G26DAO

Structure

black
red
gold

Certificazioni



LAMPING

Source	Linear LED
Total power	15W
Emission	Direct 120°
Switching	DALI
Tension	24VDC
Color temperature	3000K
Luminous flux	905lm
Initial luminaire efficacy	60m/W
Initial chromaticity	SDCM<2
Typ CRI	>97
Energy class	F
IP class	40
Dimensions	Ø20 x 1060mm
Materials	Polycarbonate
Ambient temperature range	-20°C / 50°C
Performance ambient temperature	25°C
Mechanical impact protection code	IK08
Notes	Driver included
Customization options	CCT 4000K on request
Net lamp weight	0.6 kg

Codes

BMLO1610G26WAN
BMLO1610G26WAR
BMLO1610G26WAO

Structure

black
red
gold

Certificazioni

