

Luminaire

Code FIX-LENTI
Name PARETE DOPPIA EMISSIONE


Measurem.

Code CL2920-21-02G2
Name PARETE DOPPIA EMISSIONE

Luminaire Flux	1048.79 lm	Luminaire Power	10.00 W	Efficacy	104.88 lm/W	Efficiency	100.00%
Lamps Flux	1048.79 lm	Maximum value	249.09 cd/klm	Position	C=0.00 G=2.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area	Length Diam.	100 mm 65 mm	Width Height	100 mm 0 mm	Height	30 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.003318 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.000803 m2				
Coordinate system Date Measurement Distance	CG 29-04-2021 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 180 1048.79 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Luminaire Lamps						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	FLUSSO CL29202102G2	FLUSSO CL29202102G2	1048.79	10.00	1	
C.I.E. F UTE	73 99 100 50 100 0.50 B + 0.50 T	D DIN 5040 B NBN	C61 BZ 2 / 2 / BZ 1 / 4 / BZ 2			

100mm x 100mm




Semipiani C

180.0 — 0.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %



Luminaire

Code FIX-LENTI
Name PARETE DOPPIA EMISSIONE

Measurem.

Code CL2920-21-02G2
Name PARETE DOPPIA EMISSIONE

Luminaire Flux	1048.79 lm	Luminaire Power	10.00 W	Efficacy	104.88 lm/W	Efficiency	100.00%
Lamps Flux	1048.79 lm	Maximum value	249.09 cd/klm	Position	C=0.00 G=2.00	CG	Rotosymmetrical

Luminous Intensity Table cd/klm Table 1/1

C 0.00		C 0.00	
G 0.0	249.09	G 92.0	0.26
G 2.0	249.09	G 94.0	0.31
G 4.0	248.81	G 96.0	0.35
G 6.0	248.48	G 98.0	0.39
G 8.0	247.91	G 100.0	0.44
G 10.0	247.22	G 102.0	0.50
G 12.0	246.40	G 104.0	0.57
G 14.0	245.52	G 106.0	0.66
G 16.0	244.41	G 108.0	0.79
G 18.0	243.13	G 110.0	0.93
G 20.0	241.74	G 112.0	1.11
G 22.0	240.19	G 114.0	1.31
G 24.0	238.37	G 116.0	1.57
G 26.0	236.49	G 118.0	1.96
G 28.0	234.66	G 120.0	2.65
G 30.0	232.97	G 122.0	4.17
G 32.0	231.31	G 124.0	6.99
G 34.0	229.73	G 126.0	13.44
G 36.0	228.27	G 128.0	35.17
G 38.0	226.74	G 130.0	68.82
G 40.0	224.88	G 132.0	125.16
G 42.0	221.18	G 134.0	176.35
G 44.0	208.31	G 136.0	208.31
G 46.0	176.35	G 138.0	221.18
G 48.0	125.16	G 140.0	224.88
G 50.0	68.82	G 142.0	226.74
G 52.0	35.17	G 144.0	228.27
G 54.0	13.44	G 146.0	229.73
G 56.0	6.99	G 148.0	231.31
G 58.0	4.17	G 150.0	232.97
G 60.0	2.65	G 152.0	234.66
G 62.0	1.96	G 154.0	236.49
G 64.0	1.57	G 156.0	238.37
G 66.0	1.31	G 158.0	240.19
G 68.0	1.11	G 160.0	241.74
G 70.0	0.93	G 162.0	243.13
G 72.0	0.79	G 164.0	244.41
G 74.0	0.66	G 166.0	245.52
G 76.0	0.57	G 168.0	246.40
G 78.0	0.50	G 170.0	247.22
G 80.0	0.44	G 172.0	247.91
G 82.0	0.39	G 174.0	248.48
G 84.0	0.35	G 176.0	248.81
G 86.0	0.31	G 178.0	249.09
G 88.0	0.26	G 180.0	249.09
G 90.0	0.43		